



# Modified Asphalt, All paving grades

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 11/15/2018

Supersedes: 01/01/2014

Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

**1.1. Product identifier** Other means of identification PG70-22, PG76-22, PG76-28  
 Product name : Modified Asphalt, All paving grades  
 Product form : Mixture  
 Formula : Petroleum Hydrocarbon, a complex combination of hydrocarbons having carbon numbers predominately higher than C25, and may contain hydrogen sulfide

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use of the substance/mixture : Highway paving

**1.3. Details of the supplier of the safety data sheet**

Apex Oil Company, Inc.  
Clark Oil Trading Company  
Enjet, LLC  
8235 Forsyth Boulevard, Suite 400  
St. Louis, Missouri 63105  
General Assistance 1-314-889-9600

**1.4. Emergency telephone number**

Emergency number : Chemtrec: 1-800-424-9300 (Apex reference number: 225708)

### SECTION 2: Hazard identification

**Classified Hazards**

No classified hazards

**Hazards Not Otherwise Classified (HNOC)**

PHNOC: Contact with hot product will cause thermal burns.  
Water contact with hot material can cause violent eruption

HHNOC: May contain or release poisonous hydrogen sulfide gas.

### Label Elements



**DANGER**

Water contact with hot material can cause violent eruption  
Contact with hot product will cause thermal burns.  
May contain or release poisonous hydrogen sulfide gas.

**HNOC**

Avoid overheating to minimize fume production; Keep away from any possible contact with water; Avoid breathing fumes from hot material; Use personal protective equipment as required; In case of inadequate ventilation wear respiratory protection

### SECTION 3: Composition/information on ingredients

**3.1. Substance**

Not applicable

**3.2. Mixture**

| Name                        | Product identifier | %       |
|-----------------------------|--------------------|---------|
| Bitumen                     | (CAS No) 8052-42-4 | 96 - 99 |
| Styrene-Butadiene Copolymer | (CAS No) 9003-55-8 | 1 - 4   |
| Hydrogen Sulfide            | (CAS No) 7783-06-4 | < 1     |

### SECTION 4: First aid measures

**4.1. Description of first aid measures**

First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.

First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a comfortable position for breathing.

First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes.

First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Continue rinsing.

First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention if you feel unwell.

**4.2. Most important symptoms and effects, both acute and delayed**

Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/injuries after inhalation : May cause respiratory irritation.

Symptoms/injuries after skin contact : May cause skin irritation.

# Modified Asphalt, All paving grades

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after eye contact : Direct contact with the eyes is likely to be irritating.  
Symptoms/injuries after ingestion : May cause gastrointestinal irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available.

## SECTION 5: Firefighting measures

### NFPA 704 Hazard Class

Health: 0 Flammability: 1 Instability: 0



0 (Minimal)  
1 (Slight)  
2 (Moderate)  
3 (Serious)  
4 (Severe)

**Extinguishing Media:** Dry chemical, carbon dioxide, or alcohol-resistant foam is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Water may be ineffective for extinguishment, unless used under favorable conditions by experienced fire fighters. Water fog may be used on flat surfaces such as roads. Do not use water on asphalt fire in tank or other containers since it may cause violent eruption and spreading of burning asphalt.

### Specific hazards arising from the chemical

**Unusual Fire & Explosion Hazards:** This material may burn, but will not ignite readily. This product will float and can be reignited on surface water. Vapors are heavier than air and can accumulate in low areas. When heated above its flash point, this material may release flammable vapors, which, if exposed to a source of ignition, can burn in the open or be explosive in confined spaces. Vapors released to atmosphere at these temperatures can cause flash fire. Hot asphalt may ignite flammable mixtures on contact. If water is applied to heated material, it can cause violent foaming and boil over. If container is not properly cooled, it can rupture in the heat of a fire. Hazardous combustion/decomposition products, including hydrogen sulfide, may be released by this material when exposed to heat or fire. Use caution and wear protective clothing, including respiratory protection.

**Hazardous Combustion Products:** Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Hydrogen sulfide and oxides of nitrogen and sulfur may also be formed.

**Special protective actions for fire-fighters:** For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective clothing. When the potential chemical hazard is unknown, in enclosed or confined spaces, a self contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8). Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water or foam can cause frothing. Cool equipment exposed to fire with water, if it can be done safely. Avoid spreading burning liquid with water used for cooling purposes.

See Section 9 for Flammable Properties including Flash Point and Flammable (Explosive) Limits

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Ventilate area. Keep upwind. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8).

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.  
Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.  
Methods for cleaning up : Eliminate ignition sources. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Sweep or shovel spills into appropriate container for disposal. Recover material for use if possible. This material and its container must be disposed of in a safe way, and as per local legislation.

### 6.4. Reference to other sections

See Sections 8 and 13.

# Modified Asphalt, All paving grades

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Use appropriate personal protection equipment (PPE). Use only in well-ventilated areas. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof equipment. Take precautionary measures against static discharge. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry, cool and well-ventilated place. Keep away from ignition sources. Ground and bond all transfer and storage equipment.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

No data available

#### 8.2. Exposure controls

Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment : Gloves. Protective goggles.



Hand protection : Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. . Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection : Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection : Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection : Use NIOSH-approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state : Solid  
Appearance : Viscous semi-solid to solid at room temperature.  
Color : Black.  
Odor : Hydrocarbon-asphaltic.  
Odor Threshold : Asphaltic odor at use temperatures at > 149 °C (300 °F)  
pH : No data available  
Relative evaporation rate (butylacetate=1) : No data available  
Melting point : No data available  
Freezing point : No data available

# Modified Asphalt, All paving grades

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                                 |  |
|---------------------------------|--|
| Boiling point                   | : > 900 °F / > 482 °C                            |
| Flash point                     | : > 450 °F / > 232 °C                            |
| Auto-ignition temperature       | : > 427 °C (800 °F)                              |
| Decomposition temperature       | : No data available                              |
| Flammability (solid, gas)       | : No data available                              |
| Vapor pressure                  | : < 5.17 mm Hg (0.1 psi) @ 38 °C (100 °F)        |
| Relative vapor density at 20 °C | : > 5 (Air = 1)                                  |
| Relative density                | : 1 - 1.1 @ 15 °C (60 °F) (H <sub>2</sub> O = 1) |
| Solubility                      | : Negligible.                                    |
| Log Pow                         | : No data available                              |
| Log Kow                         | : No data available                              |
| Viscosity, kinematic            | : No data available                              |
| Viscosity, dynamic              | : No data available                              |
| Explosive properties            | : No data available                              |
| Oxidising properties            | : No data available                              |
| Explosive limits                | : 0.9 - 7 vol %                                  |

### 9.2. Other information

VOC content : Negligible

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

### 10.3. Possibility of hazardous reactions

None known.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Avoid contact with : Ignition sources. Incompatible materials.

### 10.5. Incompatible materials

Oxidizing agent. Strong acids. caustic materials. Halogens.

### 10.6. Hazardous decomposition products

Thermal decomposition generates : Hydrocarbons. Carbon oxides (CO, CO<sub>2</sub>). Sulfur oxides.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

|                                   |                   |
|-----------------------------------|-------------------|
| Acute toxicity                    | : Not classified  |
| Skin corrosion/irritation         | : Not classified  |
| Serious eye damage/irritation     | : Not classified  |
| Respiratory or skin sensitisation | : Not classified  |
| Germ cell mutagenicity            | : Not classified  |
| Carcinogenicity                   | : Not classified. |

### Asphalt (8052-42-4)

|            |                                      |
|------------|--------------------------------------|
| IARC group | 2B - Possibly carcinogenic to humans |
|------------|--------------------------------------|

|  |  |
|--|--|
| Reproductive toxicity                              | : Not classified   |
| Specific target organ toxicity (single exposure)   | : Not classified   |
| Specific target organ toxicity (repeated exposure) | : Not classified   |
| Aspiration hazard                                  | : Not classified   |
| Symptoms/injuries after inhalation                 | : May cause respiratory irritation.                        |
| Symptoms/injuries after skin contact               | : May cause skin irritation.                               |
| Symptoms/injuries after eye contact                | : Direct contact with the eyes is likely to be irritating. |
| Symptoms/injuries after ingestion                  | : May cause gastrointestinal irritation.                   |

# Modified Asphalt, All paving grades

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : No information available.

#### 12.2. Persistence and degradability

| Modified Asphalt, All paving grades |                           |
|-------------------------------------|---------------------------|
| Persistence and degradability       | No information available. |

#### Modified Asphalt, All paving grades

|                           |                           |
|---------------------------|---------------------------|
| Bioaccumulative potential | No information available. |
|---------------------------|---------------------------|

#### 12.4. Mobility in soil

| Modified Asphalt, All paving grades |                           |
|-------------------------------------|---------------------------|
| Ecology - soil                      | No information available. |

#### 12.5. Other adverse effects

Other adverse effects : No data available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Obtain the consent of pollution control authorities before discharging to wastewater treatment plants.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

### SECTION 14: Transport information

Transport document description : UN3257 Elevated temperature liquid, n.o.s. (at or above 100 C and below its flash point (including molten metals, molten salts, etc.)), 9, III

UN-No.(DOT) : 3257

DOT NA no. : UN3257

Proper Shipping Name (DOT) : Elevated temperature liquid, n.o.s.  
at or above 100 C and below its flash point (including molten metals, molten salts, etc.)

Department of Transportation (DOT) Hazard Classes : 9 - Class 9 - Miscellaneous hazardous material 49 CFR 173.140

Hazard labels (DOT) : 9 - Class 9 (Miscellaneous dangerous materials)



Packing group (DOT) : III - Minor Danger

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : Forbidden

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : Forbidden

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 85 - Under deck stowage must be in mechanically ventilated space

#### Additional information

Other information : No supplementary information available.

#### Transport by sea

No additional information available

#### Air transport

No additional information available

# Modified Asphalt, All paving grades

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### Modified Asphalt, All paving grades

All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory  
All the constituents of this preparation are registered in the EINECS inventory or in the ELINCS list

SARA Section 311/312 Hazard Classes      None

##### Diethylene glycol monobutyl ether (112-34-5)

Section 302 (EHS) TPQ      500    lb

Section 304 EHS RQ      100    lb

CERCLA RQ      100    lb

Section 313      Listed on US SARA Section 313

#### 15.2. International regulations

##### CANADA

##### Modified Asphalt, All paving grades

All chemical substances in this product are listed on the Canadian DSL (Domestic Substances List)

#### 15.3. US State regulations

##### California Proposition 65

WARNING! This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

| Benz[a]acridine     | Benz[c]acridine                     | Dibenz[a,h]acridine (226-36-8) | Dibenz[a,j]acridine (224-42-0)   |
|---------------------|-------------------------------------|--------------------------------|----------------------------------|
| Carbazole (86-74-8) | 7H-Dibenzo(c,g)carbazole (194-59-2) | Dibenzothiophene               | Benzo(b)naphthol[2,1-d]thiophene |

##### Asphalt (8052-42-4)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

##### Hydrogen sulfide (7783-06-4)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

### SECTION 16: Other information

Indication of changes Revision      : Revision 1.0: New SDS Created.

date      : 03/06/2015

Other information      : Author: BCS.

#### HMIS III Rating

Health      : 0

Flammability      : 1

Physical      : 0

Personal Protection      :

Information contained herein was based on data and compiled from reference materials and other sources believed to be reliable and is offered in good faith. However, the SDS's accuracy or completeness is not guaranteed by Apex, nor is any responsibility assumed or implied for any loss or damage resulting from inaccuracies or omissions. Conditions of use and suitability of the product for particular uses are beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE IN RESPECT TO THE USE OR SUITABILITY OF THE PRODUCT. Nothing is intended as a recommendation for uses which infringe valid patents or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users.